



Quotation No. 33/25 /S.D.E.

Date: 22.12.2025

Online quotations are invited from the registered Contractor for the mentioned Work below and Quotations must be uploaded to the Secretary Board of School Education Haryana, Bhiwani by E-mail address: [ratesbsch@gmail.com](mailto:ratesbsch@gmail.com) by 02:00 PM 30.12.2025 the latest.

Name of work :- construction of 2 nos. shed after dismantling the existing condemne fibre shed in A-9.

Sr No	Description Of Items	Qty	Unit	Rates with GST
1/13.30.1	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. 13.30.1 : Hot finished welded type tubes	791.82	Kgs	
2/9.33	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length up to 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete up to any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	126.30	Sqm	
3/32.40	Providing and fixing 50 mm thick extruded polystyrene rigid insulation board of required size under deck on ceiling surface, complying with ISO 4898:2008 & ASTM C 578-08b - type VI, having thermal conductivity of 0.0289 W/m K as per ASTM C 578 (measured as per IS 3346), compressive strength of > 350 kPa listed as per ASTM D 1621, density of 34-36 kg/cum as per ASTM D 1622, water absorptions $\leq$ 1% by volume as per ASTM D 2842, oxygen index of 24.1 to 28.1 listed as per ASTM D 2863, cell size 0.4 mm of dia (max) as per ASTM D 3576. Fire retardant property as per DIN 4102, Part 1 of class B2 and as per ASTM E84 class A, fixed with suitable water based adhesive and fastener, complete in all respect as per the direction of Engineer-in-Charge.	4.65	Sqm	
4./ 12.157.1.2	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built-up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/panelling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): Powder coated aluminium (minimum thickness of powder coated 50 micron)	26.42	Kgs	
5./ 12.159.2	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. 12.159.2 With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	7.03	Sqm	
6./12.164	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	1.00	Nos	
7./12.166.2	Providing and fixing aluminium casement windows fastener of required length for aluminium windows with necessary screws etc. complete. 12.166.2 Powder coated minimum thickness 50 micron aluminium	4.00	Nos	



8./12.167.2	Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. Complete as per direction of Engineer-in charge. 12.167.2 Powder coated minium thickness 50 micron aluminium	2.00	Nos	
9./12.169.1	Filling the gap in between aluminium frame & adjacent RCC/Brick/Stone work by providing weater silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.	12.59	mtr	
10/12.88	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight up to 35 kg and door width up to 700 mm), with necessary accessories and screws etc. complete.	1.00	Nos	

### Terms & Conditions :-

1	The works shall be carried over as per PWD specifications, HSR-2021 & as desired by Engineer- in- Charge.
2	Conditionally, telegraphic quotations will not be accepted and liable to be rejected straightway.
3	All charges such as Royalty, Municipal Octroi and other all type of taxes as per Govt. Rule shall be paid by the contractor.
4	The quantity of works can be increase/decrease as per our requirements.
5	Nothing will be paid for damage done due to rain and any other act of God.
6	The successful contractor must deposit 10% security amount of contract value. Security amount will be released on request after successful completion of work.
7	Contractor has to be submitted his bill in duplicate after satisfactory completion of the work.
8	No material will be provided by the Board's office.
9	If, any other items of HSR except above mentioned will be paid same rates above or below of HSR as mentioned in work order.
10	The rates of non-schedule items shall be inclusive of fixing and installation complete in all respect and removal of old articles. All items should be ISI Mark and there shall not be extra charges for these items.
11	The unacceptable items shall be subject to replacement at the risk and the responsibility of the contractor.
12	The committee also reserves the right to relax any of the above mentioned conditions and reject all quotation altogether without assigning any reason.
13	In case of any dispute arises, the decision of the Secretary of the Board only shall be final.
14	Rate should be quoted along with G.S.T. on self letter head or in given Annexure x.

13-01-2021  
24/12/25  
Assistant Secretary(M.M.)  
HBSE, Bhiwani



Quotation Notice No 83/25/S.D.E.

Annexure: X  
Date: - 22-12-2025

Name of work :- construction of 2 nos. shed after dismantling the existing condemne fibre shed in A-9.

Sr No	Description Of Items	Qty	Unit	Quoted Rates (with GST)
1/13.30.1	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. 13.30.1 : Hot finished welded type tubes	791.82	Kgs	
2/9.33	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length up to 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete up to any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	126.30	Sqm	
3/32.40	Providing and fixing 50 mm thick extruded polystyrene rigid insulation board of required size under deck on ceiling surface, complying with ISO 4898:2008 & ASTM C 578-08b - type VI, having thermal conductivity of 0.0289 W/m K as per ASTM C 578 (measured as per IS 3346), compressive strength of > 350 kPa listed as per ASTM D 1621, density of 34-36 kg/cum as per ASTM D 1622, water absorptions ≤ 1% by volume as per ASTM D 2842, oxygen index of 24.1 to 28.1 listed as per ASTM D 2863, cell size 0.4 mm of dia (max) as per ASTM D 3576. Fire retardant property as per DIN 4102, Part 1 of class B2 and as per ASTM E84 class A, fixed with suitable water based adhesive and fastener, complete in all respect as per the direction of Engineer-in-Charge.	4.65	Sqm	
4./ 12.157.1.2	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built-up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/panelling, C.P. b rass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid for separately): Powder coated aluminium (minimum thickness of powder coated 50 micron)	26.42	Kgs	
5./ 12.159.2	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. 12.159.2 With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	7.03	Sqm	
6./12.164	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	1.00	Nos	
7./12.166.2	Providing and fixing aluminium casement windows fastener of required length for aluminium windows with necessary screws etc. complete.12.166.2 Powder coated minium thickness 50 micron aluminium	4.00	Nos	



8./12.167.2	Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. Complete as per direction of Engineer-in charge. 12.167.2 Powder coated minium thickness 50 micron aluminium	2.00	Nos	
9./12.169.1	Filling the gap in between aluminium frame & adjacent RCC/Brick/Stone work by providing weater silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.	12.59	mtr	
10/12.88	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight up to 35 kg and door width up to 700 mm), with necessary accessories and screws etc. complete.	1.00	Nos	

(Space to be used by the Quotationer for quotation the rates of the items in figure. The same is to be given back to Board by E-mail after filling up the rates) It is certified that rates of the above items is quoted by me are correct.

1. Name of Quotationer .....
2. Name of Firm/Agency/Contractor .....
3. Address Firm/Agency/Contractor .....
4. PAN No. .....
5. GST No. (Mandatory) .....
6. Mobile No./E-mail Id .....
7. Regn. No. of the firm/agency/Contractor .....
8. Beneficiary Name.....
9. Account No. of the Quotationer .....
10. I.F.S.C. Code of the Bank Branch.....
11. Name of the Bank in which Quotationer has account .....
12. Name of the Branch of the Bank .....

Signature of Quotationer  
With seal/stamp