



Quotation No. 25/25 /S.D.E.

Date: 29.08.2025

Online quotations are invited from the registered Contractor for the mentioned Work below and Quotations must be uploaded to the Secretary Board of School Education Haryana, Bhiwani by E-mail address: ratesbsch@gmail.com by 02:00 PM 05.09.2025 the latest.

Name of work :- Special Repair/ Renovation of kitchen for office Chairman & Secretary.

Sr No	Description Of Items	Qty	Unit	Rates with GST
1/5.44	Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. 5.44	1.86	Sqm	
2./10.73	Providing and fixing ceramic & Glazed tiles/ vitrified tiles/ of any size of approved make in floors / dados, laid in any pattern as specified over base of 3 mm thick adhesive of reputed brands as per IS specification 15477-2004 using 5 Kg. adhesive per sqm area of tiles and jointed with white cement slurry mixed with pigment to match the shade of tiles excluding cost of tiles. as per HSR 10.73	5.57	Sqm	
3/10.72.2	Extra for grouting the joints of floor tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting and finishing complete as per direction of Engineer-in-charge Size of Tile 600x600 mm as per HSR 10.72.2	5.57	Sqm	
4./ 8.26.2.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. 8.26.2 Granite of any colour and shade as per HSR 8.26.2.2	1.86	Sqm	
5./10.58	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. as per HSR 10.58	13.471	Sqm	
6./30.28.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:	1.95	Sqm	
7./30.25.1	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :1 Old work (one or more coats)	30.1	Sqm	
8./11.60	providing and applying white cement based putty of average 1mm thickness as per HSR 11.60	30.1	Sqm	

Terms & Conditions :-

1	The works shall be carried over as per PWD specifications, HSR-2021 & as desired by Engineer- in- Charge.
2	Conditionally, telegraphic quotations will not be accepted and liable to be rejected straightway.
3	All charges such as Royalty, Municipal Octroi and other all type of taxes as per Govt. Rule shall be paid by the contractor.
4	The quantity of works can be increase/decrease as per our requirements.



5	Nothing will be paid for damage done due to rain and any other act of God.
6	The successful contractor must deposit 10% security amount of contract value. Security amount will be released on request after successful completion of work.
7	Contractor has to be submitted his bill in duplicate after satisfactory completion of the work.
8	No material will be provided by the Board's office.
9	If, any other items of HSR except above mentioned will be paid same rates above or below of HSR as mentioned in work order.
10	The rates of non-schedule items shall be inclusive of fixing and installation complete in all respect and removal of old articles. All items should be ISI Mark and there shall not be extra charges for these items.
11	The unacceptable items shall be subject to replacement at the risk and the responsibility of the contractor.
12	The committee also reserves the right to relax any of the above mentioned conditions and reject all quotation altogether without assigning any reason.
13	In case of any dispute arises, the decision of the Secretary of the Board only shall be final.
14	Rate should be quoted along with G.S.T. on self letter head or in given Annexure x.

13-08-23
28/08/23
Assistant Secretary(M.M.)
HBSE, Bhiwani



Annexure: X

Date: - 29.08.2025

Quotation Notice No. 2815/S.D.E.

Name of work :- Special Repair/ Renovation of kitchen for office Chairman & Secretary.

Sr No	Description Of Items	Qty	Unit	Quoted Rates (with GST)
1/5.44	Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. 5.44	1.86	Sqm	
2./10.73	Providing and fixing ceramic & Glazed tiles/ vitrified tiles/ of any size of approved make in floors / dados, laid in any pattern as specified over base of 3 mm thick adhesive of reputed brands as per IS specification 15477-2004 using 5 Kg. adhesive per sqm area of tiles and jointed with white cement slurry mixed with pigment to match the shade of tiles excluding cost of tiles. as per HSR 10.73	5.57	Sqm	
3/10.72.2	Extra for grouting the joints of floor tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting and finishing complete as per direction of Engineer-in-charge Size of Tile 600x600 mm as per HSR 10.72.2	5.57	Sqm	
4./ 8.26.2.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. 8.26.2 Granite of any colour and shade as per HSR 8.26.2.2	1.86	Sqm	
5./10.58	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. as per HSR 10.58	13.471	Sqm	
6./30.28.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:	1.95	Sqm	
7./30.25.1	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :1 Old work (one or more coats)	30.1	Sqm	
8./11.60	providing and applying white cement based putty of average 1mm thickness as per HSR 11.60	30.1	Sqm	

(Space to be used by the Quotationer for quotation the rates of the items in figure. The same is to be given back to Board by E-mail after filling up the rates) It is certified that rates of the above items is quoted by me are correct.

1. Name of Quotationer
2. Name of Firm/Agency/Contractor.....



3. Address Firm/Agency/Contractor.....
4. PAN No.
5. GST No. (Mandatory)
6. Mobile No./E-mail Id
7. Regn. No. of the firm/agency/Contractor
8. Beneficiary Name.....
9. Account No. of the Quotationer
10. I.F.S.C. Code of the Bank Branch.....
11. Name of the Bank in which Quotationer has account
12. Name of the Branch of the Bank

Signature of Quotationer
With seal/stamp