



Quotation No. 14/25 /S.D.E.

Date: 14.05.2025

Online quotations are invited from the registered Contractor for the mentioned Work below and Quotations must be uploaded to the Secretary Board of School Education Haryana, Bhiwani by E-mail address: ratesbseh@gmail.com by 02:00 PM 22.05.2025 the latest.

Name of work:- **Painting, Granite work, wall tile, wooden door and toughned glass door etc. in Canteen.**

Sr No	Description Of Items	Qty	Unit	Rates with GST
1/5.44	Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. 5.44	15.61	Sqm	
2./5.30.1	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead :	3.00	nos.	
3/10.73	Providing and fixing ceramic & Glazed tiles/ vitrified tiles/ of any size of approved make in floors / dados, laid in any pattern as specified over base of 3 mm thick adhesive of reputed brands as per IS specification 15477-2004 using 5 Kg. adhesive per sqm area of tiles and jointed with white cement slurry mixed with pigment to match the shade of tiles excluding cost of tiles. as per HSR 10.73	10.78	Sqm	
4./10.70.2	Extra for grouting the joints of floor tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting and finishing complete as per direction of Engineer-in-charge. Size of Tile 600x600 mm as per HSR 10.72.2	10.78	Sqm	
5./8.26.2.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. 8.26.2 Granite of any colour and shade as per HSR 8.26.2.2	12.40	Sqm	
6./5.45	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	25.05	Sqm	
7./30.16.1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.	5.00	Sqm	
8./10.58	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. as per HSR 10.58	30.61	Sqm	
9./10.104	Mirror polishing on marble work/Granite work/stone work wherever required to give high gloss finish complete. As per HSR 10.104	122.63	Sqm	
10./ 12.171	Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top & bottom pivot & double acting hydraulic floor spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-in-charge (Door handle, lock and stopper etc.to be paid separately).	3.90	Sqm	



11./ 12.36.2	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. As per HSR 12.36.212.36.2 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	6.90	Sqm	
12/ 12.40.1	Extra for providing vision panel not exceeding 0.1 sqm in all type of flush doors (cost of glass excluded) (overall area of door shutter to be measured): 1 Rectangular or square	5.02	sqm	
13/ 12.173	Providing and fixing bright finished 100 mm mortice lock with 6 levers without pair of handles of approved quality for aluminium door, with necessary screws etc complete as per direction of Engineer- in-charge.	2.00	Nos.	
14./ 30.28.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :	84.17	Sqm	
15/ 30.25.1	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :1 Old work (one or more coats)	150.00	Sqm	
16/N.S.	Providing and fixing Stainless steel glass door handle of size 400mmx150mmx22mm complete in all respects	1.00	Nos.	
17/N.S.	Providing and fixing 12mm thick toughened glass partition work with dotted film and sliding opening/fixed type including all required accessories for fixing complete in all respects.	4.63	sqm	

Terms & Conditions :-

1	The works shall be carried over as per PWD specifications, HSR-2021 & as desired by Engineer- in- Charge.
2	Conditionally, telegraphic quotations will not be accepted and liable to be rejected straightway.
3	All charges such as Royalty, Municipal Octroi and other all type of taxes as per Govt. Rule shall be paid by the contractor.
4	The quantity of works can be increase/decrease as per our requirements.
5	Nothing will be paid for damage done due to rain and any other act of God.
6	The successful contractor must deposit 10% security amount of contract value. Security amount will be released on request after successful completion of work.
7	Contractor has to be submitted his bill in duplicate after satisfactory completion of the work.
8	No material will be provided by the Board's office.
9	If, any other items of HSR except above mentioned will be paid same rates above or below of HSR as mentioned in work order.
10	The rates of non-schedule items shall be inclusive of fixing and installation complete in all respect and removal of old articles. All items should be ISI Mark and there shall not be extra charges for these items.
11	The unacceptable items shall be subject to replacement at the risk and the responsibility of the contractor.
12	The committee also reserves the right to relax any of the above mentioned conditions and reject all quotation altogether without assigning any reason.
13	In case of any dispute arises, the decision of the Secretary of the Board only shall be final.
14	Rate should be quoted along with G.S.T. on self letter head or in given Annexure x.

14.5.2025
Assistant Secretary(M.M.)
HBSE, Bhiwani



Quotation Notice No 14125/S.D.E.

Annexure: X
Date: - 14.05.2025

Name of work:- **Painting, Granite work, wall tile, wooden door and toughened glass door etc. in Canteen.**

Sr No	Description Of Items	Qty	Unit	Quoted Rates (with GST)
1/5.44	Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 metres lead. 5.44	15.61	Sqm	
2./5.30.1	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead :	3.00	nos.	
3/10.73	Providing and fixing ceramic & Glazed tiles/ vitrified tiles/ of any size of approved make in floors / dados, laid in any pattern as specified over base of 3 mm thick adhesive of reputed brands as per IS specification 15477-2004 using 5 Kg. adhesive per sqm area of tiles and jointed with white cement slurry mixed with pigment to match the shade of tiles excluding cost of tiles. as per HSR 10.73	10.78	Sqm	
4./10.70.2	Extra for grouting the joints of floor tiles having joints of 3 mm width, using epoxy grout mix of 0.70 kg of organic coated filler of desired shade (0.10 kg of hardener and 0.20 kg of resin per kg), including filling / grouting and finishing complete as per direction of Engineer-in-charge. Size of Tile 600x600 mm as per HSR 10.72.2	10.78	Sqm	
5./8.26.2.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. 8.26.2 Granite of any colour and shade as per HSR 8.26.2.2	12.40	Sqm	
6./5.45	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	25.05	Sqm	
7./30.16.1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.	5.00	Sqm	
8./10.58	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. as per HSR 10.58	30.61	Sqm	
9./10.104	Mirror polishing on marble work/Granite work/stone work wherever required to give high gloss finish complete. As per HSR 10.104	122.63	Sqm	
10./12.171	Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top & bottom pivot & double acting hydraulic floor spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-in-charge (Door handle, lock and stopper etc.to be paid separately).	3.90	Sqm	



11./ 12.36.2	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. As per HSR 12.36.212.36.2 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	6.90	Sqm	
12/ 12.40.1	Extra for providing vision panel not exceeding 0.1 sqm in all type of flush doors (cost of glass excluded) (overall area of door shutter to be measured): 1 Rectangular or square	5.02	sqm	
13/ 12.173	Providing and fixing bright finished 100 mm mortice lock with 6 levers without pair of handles of approved quality for aluminium door, with necessary screws etc complete as per direction of Engineer- in-charge.	2.00	Nos.	
14./ 30.28.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :	84.17	Sqm	
15/ 30.25.1	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade :1 Old work (one or more coats)	150.00	Sqm	
16/N.S.	Providing and fixing Stainless steel glass door handle of size 400mmx150mmx22mm complete in all respects	1.00	Nos.	
17/N.S.	Providing and fixing 12mm thick toughened glass partition work with dotted film and sliding opening/fixed type including all required accessories for fixing complete in all respects.	4.63	sqm	

(Space to be used by the Quotationer for quotation the rates of the items in figure. The same is to be given back to Board by E-mail after filling up the rates) It is certified that rates of the above items is quoted by me are correct.

1. Name of Quotationer
2. Name of Firm/Agency/Contractor.....
3. Address Firm/Agency/Contractor.....
4. PAN No.
5. GST No. (Mandatory)
6. Mobile No./E-mail Id
7. Regn. No. of the firm/agency/Contractor
8. Beneficiary Name.....
9. Account No. of the Quotationer
10. I.F.S.C. Code of the Bank Branch.....
11. Name of the Bank in which Quotationer has account
12. Name of the Branch of the Bank

Signature of Quotationer
With seal/stamp